



Ecospot Mini

8 980 055 019

3 W, 157 lm, 4000 K neutral white,
narrow beam 4°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of die-cast aluminum ALSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, silicon gasket, with 3 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 2 drilled holes \varnothing 7 mm, spacing 30 mm, 1 centre hole \varnothing 8.5 mm, tilt range: 140° , cable gland: M20, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), 80, max 2 SDCM, service life $L_{90/B_{10}} > 50.000$ h, Beam angle (FWHM): 4° , luminous flux: 157 lm, wattage: 3 W, delivered lumens 52 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,01 m², dimensions: \varnothing 75 mm, width 125 mm, weight 0.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

| | | | |
|----------------------------|----------------------------|-----------------------------|-----------------------------------|
| Wattage | 3 W | Beam angle (FWHM) | 4° |
| Delivered lumens | 52 lm/W | Housing colour | silver grey |
| Light source | LED 4000 K | Power supply cable | \varnothing 6 – 13 mm |
| Color Rendering Index | 80 | Protection type | IP65 |
| Colour tolerance | max 2 SDCM | Protection class | I |
| Lifetime ta 25° C | $L_{90/B_{10}} > 50.000$ h | Impact resistance | IK08 |
| Control gear | on / off | Windage area | 0,01m ² |
| Input voltage AC | 100 – 240 V | Dimensions | \varnothing 75 mm, width 125 mm |
| Input voltage DC | 134 – 335 V | Weight | 0,80 kg |
| Voltage protection | 1 kV L/N 1 kV L/PE | Max. ambient temperature ta | 40° |
| Luminaires per B16A / C16A | 157 / 317 | | |