



## Fluxa A

8 284 066 079

2 × 20 W, 3950 lm, 3000 K warm white,  
wide beam  $62^\circ / 130^\circ$



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, with prismatic glass for reduced glare, silicon gasket, closure with 4 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 4 holes  $\varnothing 8.5 \text{ mm}$ , spacing 70 mm (120 mm), 2 drilled holes  $\varnothing 10 \text{ mm}$ , spacing 200 mm, 1 centre hole  $\varnothing 22 \text{ mm}$ , tilt range:  $210^\circ$ , cable gland: M20, connecting terminal: 3 pole, highly efficient anodized rotationally symmetrical reflector with matt finish, integral control gear, CRI > 70, max 2 SDCM, service life  $L_{90}/B_{10} > 50.000 \text{ h}$ , Beam angle (FWHM):  $62^\circ / 130^\circ$ , luminous flux: 3950 lm, wattage: 40 W, delivered lumens 99 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area  $0,11 \text{ m}^2$ , dimensions (L×H×W):  $380 \times 131 \times 280 \text{ mm}$ , weight 6.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



## Specification

Wattage	40 W	Beam angle (FWHM)	$62^\circ / 130^\circ$
Delivered lumens	99 lm/W	Housing colour	white RAL 9002
Light source	LED 3000 K	Power supply cable	$\varnothing 8 - 1.5 \text{ mm}$
Color Rendering Index	CRI > 70	Protection type	IP67
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta $25^\circ \text{ C}$	$L_{90}/B_{10} > 50.000 \text{ h}$	Impact resistance	IK08
Control gear	on / off	Windage area	$0,11 \text{ m}^2$
Input voltage AC	170 – 260 V	Dimensions	$380 \times 131 \times 280 \text{ mm}$
Input voltage DC	176 – 276 V	Weight	6,20 kg
Voltage protection	6 kV L/N   10 kV L/PE	Max. ambient temperature ta	$45^\circ$
Luminaires per B16A / C16A	12 / 0		