





## Fluxa A

8 285 345 149

48 W, 5713 lm, 4000 K neutral white, DALI, asymmetrical 60°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, with single pole top fitter, for pole top  $\varnothing 60/76$ mm, with 8m rubber cable Ho5RN-F5G1, cable gland: M20, connecting terminal: 5 pole, highly efficient anodized rotationally symmetrical reflector with matt finish, integral driver (DALI / Step Dim / Astro Dim), CRI > 70, max 2 SDCM, service life L90/B10 > 50.000 h, luminous flux: 5713 lm, wattage: 48 W, delivered lumens 119 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,11 m<sup>2</sup>, dimensions (L×H×W): 380 × 131 × 280 mm, weight 6.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP 67 IK 08

## Specification

|                            |                       |                             |                         |
|----------------------------|-----------------------|-----------------------------|-------------------------|
| Wattage                    | 48 W                  | Housing colour              | black RAL 7021          |
| Delivered lumens           | 119 lm/W              | Power supply cable          | $\varnothing 8 - 15$ mm |
| Light source               | LED 4000 K            | Protection type             | IP67                    |
| Color Rendering Index      | CRI > 70              | Protection class            | I                       |
| Colour tolerance           | max 2 SDCM            | Impact resistance           | IK08                    |
| Lifetime ta 25° C          | L90/B10 > 50.000 h    | Windage area                | 0,11 m <sup>2</sup>     |
| Control gear               | DALI                  | Dimensions                  | 380 × 131 × 280 mm      |
| Input voltage AC           | 170 – 260 V           | Weight                      | 6,60 kg                 |
| Input voltage DC           | 176 – 276 V           | Max. ambient temperature ta | 45°                     |
| Voltage protection         | 6 kV L/N   10 kV L/PE |                             |                         |
| Luminaires per B16A / C16A | 12 / 0                |                             |                         |