






## Gemini 2

8 338 258 009

8 × 2,5 W, 870 lm, 3000 K warm white,  
wide beam up, asymmetrical beam down  
up 45° / asymmetrical down°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, wall box: 2 drilled holes Ø 6 mm, spacing 75 mm, two cable entries for recessed or surface mounted cable Ø 7-10 mm, cable gland: 2 x up to Ø 7-10 mm, recessed or surface mounted cable, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): up 45° / asymmetrical down°, luminous flux: 870 lm, wattage: 20 W, delivered lumens 44 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,017 m<sup>2</sup>, dimensions (L×H×W): 81 × 164 × 105 mm, weight 1.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

## Specification

|                            |                      |                             |                             |
|----------------------------|----------------------|-----------------------------|-----------------------------|
| Wattage                    | 20 W                 | Beam angle (FWHM)           | up 45° / asymmetrical down° |
| Delivered lumens           | 44 lm/W              | Housing colour              | silver grey                 |
| Light source               | LED 3000 K           | Power supply cable          | Ø 7 – 10 mm                 |
| Color Rendering Index      | CRI > 80             | Protection type             | IP65                        |
| Colour tolerance           | max 2 SDCM           | Protection class            | I                           |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Impact resistance           | IK08                        |
| Control gear               | on / off             | Windage area                | 0,017m <sup>2</sup>         |
| Input voltage AC           | 220 – 240 V          | Dimensions                  | 81 × 164 × 105 mm           |
| Input voltage DC           | 190 – 255 V          | Weight                      | 1,20 kg                     |
| Voltage protection         | 2 kV L/N   4 kV L/PE | Max. ambient temperature ta | 40°                         |
| Luminaires per B16A / C16A | 50 / 85              |                             |                             |