


Metaspace

8 217 346 399 6 × 8,6 W, 6529 lm, 3000 K warm white, Zhaga 18 up,

Street Optic 36° / 155°





Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification

Wattage 52 W Beam angle (FWHM) Delivered lumens 126 lm/W Housing colour Light source LED 3000 K Protection type Color Rendering Index CRI > 80 Protection class Ш Colour tolerance Impact resistance 3 Lifetime ta 25° C L80/B20 > 50.000 h Dimensions Control gear Zhaga 18 - oben Weight



Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminarie for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, PMMA Linsen, integral driver (AC/DC), CRI > 80, 3, service life L80/B20 > 50.000 h, Beam angle (FWHM): 36° / 155°, luminous flux: 6529 lm, wattage: 52 W, delivered lumens 126 lm/W, protection type IP65, protection class II, impact resistance IK08, dimensions: Ø 376 mm, width 112 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



36° / 155° black RAL 7021 IP65 II IK08 Ø 376 mm, width 112 mm 5,00 kg