




## Metaspot 3

8 243 269 059

49 W, 1937 lm, RGBW (3000 K) warm white, DMX, wide beam 57°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, tool-free twist closure, for installation on poles  $\varnothing$  60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes  $\varnothing$  9 mm, spacing 95 mm, 1 centre hole  $\varnothing$  40 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 6 pole, light source completely shielded, high gloss aluminium reflector, integral driver (AC/DC), Beam angle (FWHM): 57°, luminous flux: 1937 lm, wattage: 49 W, delivered lumens 40 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,055 m<sup>2</sup>, dimensions:  $\varnothing$  201 mm, width 272 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

## Specification

|                            |                   |                             |                                    |
|----------------------------|-------------------|-----------------------------|------------------------------------|
| Wattage                    | 49 W              | Beam angle (FWHM)           | 57°                                |
| Delivered lumens           | 40 lm/W           | Housing colour              | white RAL 9002                     |
| Light source               | LED RGBW (3000 K) | Power supply cable          | $\varnothing$ 6 – 11 mm            |
| Control gear               | DMX               | Protection type             | IP65                               |
| Input voltage AC           | 120 – 277 V       | Protection class            | I                                  |
| Input voltage DC           | 120 – 250 V       | Impact resistance           | IK08                               |
| Luminaires per B16A / C16A | 22 / 22           | Windage area                | 0,055m <sup>2</sup>                |
|                            |                   | Dimensions                  | $\varnothing$ 201 mm, width 272 mm |
|                            |                   | Weight                      | 5,00 kg                            |
|                            |                   | Max. ambient temperature ta | 35°                                |