









## Monoline 2

8~781~145~089  $6\times4,7$  W, 2122 lm, 4000 K neutral white, asymmetrical  $35\,^{\circ}$ 







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## **Specification text**

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, with partial frosting for uniform light diffraction and dark silk-print, silicon gasket, closure with 4 stainless steel screws, wall bracket: 2 drilled holes Ø 7 mm, spacing 35 mm, tilt range: 180°, cable gland: M20, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), CRI > 80, max 3 SDCM, service life L80/B20 > 50.000 h, luminous flux: 2122 lm, wattage: 28 W, delivered lumens 76 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,032 m², dimensions (L×H×W): 472 × 50 × 62 mm, weight 2.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

black RAL 7021 Ø 6 – 13 mm

472 × 50 × 62 mm

IP65

IK08 0,032m<sup>2</sup>

2,10 kg 35°



IP65 IK08

## Specification

Wattage	28 W	Housing colour	ŀ
Delivered lumens	76 lm/W	Power supply cable	(
Light source	LED 4000 K	Protection type	I
Color Rendering Index	CRI > 80	Protection class	I
Colour tolerance	max 3 SDCM	Impact resistance	I
Lifetime ta 25° C	L80/B20 > 50.000 h	Windage area	(
Control gear	on / off	Dimensions	2
Input voltage AC	220 - 240 V	Weight	
Input voltage DC	200 – 240 V	Max. ambient temperature ta	
Voltage protection	2 kV L/N   2 kV L/PE		
Luminaires per B16A / C16A	50 / 85		