


Monospace

8 252 455 189

10 \times 10,8 W, 13950 lm, 4000 K neutral white, DALI, asymmetrical wide beam 60° / 138°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, with pole top fitter for 2 luminaires for poles Ø 60/76 mm, 3 M8 grub screws, tilt range: 7°, cable gland: M20, with 2x 8 m cable Ho5RN-F5G1, connecting terminal: 5 pole, highly efficient metallized PC reflector, integral driver (DALI), CRI > 80, 3 SCDM, service life L80/B20 > 50.000 h,

Beam angle (FWHM): $60^{\circ}/138^{\circ}$, luminous flux: 13950 lm, wattage: 108 W, delivered lumens 129 lm/W, protection type IP67, protection class II, impact resistance IK08, windage area 0,063 m², dimensions (L×H×W): $924\times67\times308$ mm, weight 9.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





Max. ambient temperature ta

IP67 IK08

Specification

Wattage 108 W

Delivered lumens 129 lm/W

Light source LED 4000 K

Color Rendering Index CRI > 80

Colour tolerance 3 SCDM

Lifetime ta 25° C L80/B20 > 50.000 h

Control gear DALI

60° / 138° Beam angle (FWHM) Housing colour silver grey Power supply cable \emptyset 5 - 14 mm Protection type IP67 Protection class Impact resistance **IK08** Windage area $0.063 \,\mathrm{m}^2$ Dimensions 924 × 67 × 308 mm Weight 9,70 kg

35°