



Monospot 3

8 903 046 299

36 W, 2938 lm, 3000 K warm white, 1-10V, asymmetrical 18°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, mounting bracket: 2 drilled holes \varnothing 7 mm, spacing 30-40 mm, 1 centre hole \varnothing 17 mm, tilt range: 180°, cable gland: M20, connecting terminal: 5 pole, high efficiency asymmetrical aluminum reflector, integral driver (dimnable 1-10V), CRI > 80, max 2 SCDM, service life L90/B10 > 50.000 h, luminous flux: 2938 lm, wattage: 36 W, delivered lumens 83 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,049 m², dimensions: \varnothing 175 mm, width 200 mm, weight 3.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP67 IK08

Specification

| | | | |
|----------------------------|----------------------|-----------------------------|------------------------------------|
| Wattage | 36 W | Housing colour | black RAL 7021 |
| Delivered lumens | 83 lm/W | Power supply cable | \varnothing 6 – 13 mm |
| Light source | LED 3000 K | Protection type | IP67 |
| Color Rendering Index | CRI > 80 | Protection class | I |
| Colour tolerance | max 2 SCDM | Impact resistance | IK08 |
| Lifetime ta 25° C | L90/B10 > 50.000 h | Windage area | 0,049m ² |
| Control gear | 1-10V | Dimensions | \varnothing 175 mm, width 200 mm |
| Input voltage AC | 110 – 240 V | Weight | 3,50 kg |
| Input voltage DC | 190 – 250 V | Max. ambient temperature ta | 35° |
| Voltage protection | 4 kV L/N 5 kV L/PE | | |
| Luminaires per B16A / C16A | 30 / 51 | | |