



## Nanocube

8 308 246 029 5 W, 348 lm, 3000 K warm white, linear beam spread 34° / 7°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, housing locked with a grub screw, ceiling mounting: 2 drilled holes Ø 4.5 mm, spacing 35 mm, cable gland:

cable entry for recessed cable  $\varnothing$  7-10 mm , connecting terminal: 3 pole, highly efficient aluminum reflector for linear beam spread, integral driver (AC/DC), CRI > 80, max 3 SDCM, service life L90/B10 > 50.000 h,

Beam angle (FWHM):  $34^{\circ}$  /  $7^{\circ}$ , luminous flux: 348 lm, wattage: 5 W, delivered lumens 70 lm/W, protection type IP65, protection class I, impact resistance IK07, windage area 0,005 m², dimensions (L×H×W):  $66 \times 87 \times 66$  mm, weight 0.57 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

34°/7°

IP65

IK07

 $0,005m^2$ 

0,57 kg

45°

66 × 87 × 66 mm

black RAL 7021



IP65 IK07

## Specification

5 W Wattage Beam angle (FWHM) Delivered lumens 70 lm/W Housing colour Protection type Light source LED 3000 K Color Rendering Index CRI > 80 Protection class max 3 SDCM Impact resistance Colour tolerance L90/B10 > 50.000 h Lifetime ta 25° C Windage area Control gear on / off Dimensions Weight Input voltage AC 100 – 240 V Max. ambient temperature ta 1 kV L/N | 1 kV L/PE Voltage protection Luminaires per B16A / C16A 154 / 154