


## Superlight Compact

8 861 347 469

For ceramic metal halide lamps (HIT-CE)



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 2 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 2 drilled holes  $\text{\O} 8.5 \text{ mm}$ , spacing 70 mm, 1 centre hole  $\text{\O} 17 \text{ mm}$ , tilt range:  $120^\circ$ , cable gland: 2 x PG 11, cable entry: 2, connecting terminal: 3 pole, rotationally symmetrical satin finish aluminum reflector, integral ballast and ignitor, LPF, HPF available on request, Beam angle (FWHM):  $32^\circ$ , luminous flux: 3300 lm, wattage: 35 W, delivered lumens 79 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area  $0,04 \text{ m}^2$ , dimensions (LxHxW):  $170 \times 245 \times 192 \text{ mm}$ , weight 3.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

## Specification

|                  |          |                    |  |
|------------------|----------|--------------------|--|
| Wattage          | 35 W     | Beam angle (FWHM)  | $32^\circ$                             |
| Delivered lumens | 79 lm/W  | Housing colour     | black RAL 7021                         |
| Control gear     | on / off | Power supply cable | $\text{\O} 5 - 13 \text{ mm}$          |
|                  |          | Protection type    | IP65                                   |
|                  |          | Protection class   | I                                      |
|                  |          | Impact resistance  | IK08                                   |
|                  |          | Windage area       | $0,04 \text{ m}^2$                     |
|                  |          | Dimensions         | $170 \times 245 \times 192 \text{ mm}$ |
|                  |          | Weight             | 3,70 kg                                |