





## Superlight Nano 1

8 817 066 039

2.5 W, 150 lm, 3000 K warm white,  
linear horizontal 8° / 51°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of die-cast aluminum ALSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, powder coated die cast zinc mounting bracket with tilt scale: 2 drilled holes  $\varnothing 7$  mm, spacing 30 mm, 1 centre hole  $\varnothing 11$  mm, tilt range: 120°, cable gland: M16, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 8° / 51°, luminous flux: 150 lm, wattage: 2.5 W, delivered lumens 58 lm/W, protection type IP67, protection class I, impact resistance IK07, windage area 0,006 m<sup>2</sup>, dimensions (L×H×W): 60 × 80 × 60 mm, weight 0.463 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP67 IK07

## Specification

|                            |                      |                             |                        |
|----------------------------|----------------------|-----------------------------|------------------------|
| Wattage                    | 2.5 W                | Beam angle (FWHM)           | 8° / 51°               |
| Delivered lumens           | 58 lm/W              | Housing colour              | white RAL 9002         |
| Light source               | LED 3000 K           | Power supply cable          | $\varnothing 5 - 9$ mm |
| Color Rendering Index      | CRI > 80             | Protection type             | IP67                   |
| Colour tolerance           | max 2 SDCM           | Protection class            | I                      |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Impact resistance           | IK07                   |
| Control gear               | on / off             | Windage area                | 0,006m <sup>2</sup>    |
| Input voltage AC           | 100 – 240 V          | Dimensions                  | 60 × 80 × 60 mm        |
| Input voltage DC           | 195 – 240 V          | Weight                      | 0,46 kg                |
| Voltage protection         | 2 kV L/N   2 kV L/PE | Max. ambient temperature ta | 45°                    |
| Luminaires per B16A / C16A | 50 / 85              |                             |                        |